

11 **ᐱᐱᐱᐱᐱᐱ ᐱᐱᐱᐱ ᐱᐱᐱᐱ ᐱᐱᐱ ᐱᐱᐱᐱᐱ ᐱᐱᐱᐱᐱ**


ᐱᐱᐱᐱᐱ ᐱᐱᐱᐱᐱᐱ ᐱᐱᐱᐱᐱᐱ ᐱᐱᐱᐱᐱ ᐱᐱᐱᐱ ᐱᐱᐱᐱ ᐱᐱᐱᐱ ᐱᐱᐱᐱ ᐱᐱᐱᐱ ᐱᐱᐱᐱᐱ ᐱᐱᐱ Cupwind ᐱᐱᐱᐱᐱᐱ ᐱᐱᐱᐱᐱᐱ ᐱᐱᐱᐱ ᐱᐱᐱᐱᐱᐱ ᐱᐱᐱᐱᐱᐱ ᐱᐱᐱᐱ ᐱᐱᐱᐱᐱᐱ ᐱᐱᐱᐱ ᐱᐱᐱᐱᐱᐱ.



3 ᐱᐱᐱᐱᐱᐱ ᐱᐱᐱᐱᐱᐱ ᐱᐱᐱᐱᐱᐱ ᐱᐱᐱᐱᐱ ᐱᐱᐱᐱ ᐱᐱᐱᐱ ᐱᐱᐱᐱ ᐱᐱᐱᐱᐱᐱ ᐱᐱᐱᐱᐱ ᐱᐱᐱ ᐱᐱ ᐱᐱᐱᐱᐱ ᐱᐱᐱᐱᐱᐱ ᐱᐱᐱᐱᐱᐱ ᐱᐱᐱᐱ ᐱᐱᐱᐱᐱᐱ ᐱᐱᐱᐱ ᐱᐱᐱᐱᐱᐱ 180-160 ᐱᐱᐱ ᐱᐱᐱᐱᐱᐱ ᐱᐱᐱᐱᐱ ᐱᐱᐱᐱᐱᐱ ᐱᐱ ᐱᐱᐱᐱᐱᐱ ᐱᐱᐱᐱᐱᐱ.



این تصویر برای استفاده در وبسایت شما قرار داده شده است. [این لینک](#) را در قسمت توضیحات محصول خود قرار دهید. همچنین می توانید این تصویر را در شبکه های اجتماعی خود به اشتراک بگذارید.



此报告是根据客户要求，对样品进行了测试。测试结果如下：48 小时内，样品在测试过程中没有出现任何异常。所有测试项目均符合标准要求。本报告仅供参考，不作为法律依据。如有需要，请咨询相关机构。



TEST REPORT



(8521)097-0435
Page 3 of 4

SHENZHEN JIERUMA TRADING CO., LTD
NO.415 RUNLIAN BUILDING, SHENZHU ROAD,
HENGANG, 518115, SHENZHEN, CHINA

LAB LOCATION: SHENZHEN
LAB NUMBER: (8521)097-0435

ATTN: EMMA ZOU
CC: emma@cupwind.com

DATE IN: APR 07, 2021
MOD. LOG IN: /
DATE OUT: APR 13, 2021
REVISED DATE: /
WORKING DAYS: 5
PAGE: 2 OF 4

OVERALL RATING

PASS X
FAIL
DATA

TESTING FOR
CA 65 LEAD & CADMIUM ON NON-FOOD /
BEVERAGE GLASSWARE-EXTERIOR

Sample Description:	IRIDESCENT COATING CANDLE JAR		
Manufacturer:	CUPWIND COOPERATED FACILITY	P.O. No.:	/
Buyer:	IPSY	Style:	/
Country of Origin:	CHINA	Country of Destination:	USA
Color:	IRIDESCENT	SKU Number:	ITEM#: 8090
Brand name:	CUPWIND 8		
Re-test:	Yes: ☐ No: ☒	Charge Vendor:	Yes: ☒ No: ☐
Previous Report No.:	/		

EXECUTIVE SUMMARY:

Test content	Result/Rating
CA 65 Lead & Cadmium on non-food/beverage glassware-exterior	Meet/Pass

Effectiveness of annealing	ASTM F2179-20 Sec. 4.2 (Mod)	With a tungsten carbide scribe, scratch once around the inside knuckle of the article. Then scratch an "X" across the entire inside bottom surface of the article. All scratches are to be made using sufficient pressure to just penetrate the surface of the glass. Fill each article with water at the same room temperature as the glass. Wait 15 minutes, then empty the water and examine each piece for fractures. Shall show no fractures. Report the number of fractures, if any, for each test. Modification: expanded scope to all other glass products in addition to candle containers.	M	PASS
Thermal shock	ASTM F2179-20 Sec. 4.2 (Mod) / ASTM C149	Shall not crack or break after tested per below: - prepare a cold-water bath at 21±1.1°C (70±2°F). - prepare a hot bath at 71±1.1°C (160±2°F) - Immerse the sample completely in the hot water bath and allow to soak for 5 min ± 10 s. - transfer the sample to the cold bath, and immerse for at least 30 s. - remove the sample from the cold bath and examine the sample for any cracking. Note: - the hot water that collects within the container during the first immersion shall be retained in the container through the second immersion - the time of transfer from the hot bath to the cold bath shall be 15 ± 1 s Modification: sampling procedure not followed and expanded scope to all other glass products in addition to candle containers.	M	PASS

REMARK:

- No enclosed protocol for test results in this report.

000000 0000 000000000000 .0000 000 000 00 000000 0000 0000 000000000 000000 00000 0000 0000000 000
 0000000000 000000000 000000000 000000000 000000000 000 0000000 Cali 65 Pro 00000000000 0000000 0000000000.