

□□□□□ □□□□□ □□□□□ □□□□□ □□□□ □□□□ □□□□□

[illegible]

0000000 0000000

00 00000000 00000000 00000000 000000 00000 000000 000000 00 00000 00000 00 000000 00000000 0000
 00 0000000 00000000 0000000000 0000 00000 00 0000000000 00000000 00000 00000 000000 00000000
 0000 000000000 00000000 00000 0000000 0000 00000000 00000000 000000000 0000 0000000000 0000000000 Nest
 Fragrance 0Voluspa 00000000 00000000 0000000 0000000000 00000000000 00000000000 0000 .0000 0000 0000
 0000 0000 0000 00000000 0000000000 00000 0000000000 0000000 00 00000000.

00000

- .00000 :0000000
- 00000 00000 0000000000 0000000 :00000000 -
- .0000000 00000 0000000 00 0000000 00000 -
- 3 00000000 00000000 00000000 -M6160 .0000000000 00000000 0000000 00000000 0000000000
- 00000000 0000000000 00000000 0000000000 00000 0000 00000000 0000000 0000 000000000000 000000 0000000000 00000 -
- 0000 0000 0000 00000000 00000000 0000000 00000000.





[illegible][illegible][illegible][illegible]

Cupwind

ASTM D1505 標準に準拠

Cupwind は、ASTM D1505 標準に準拠した、ガラスの熱膨張率を測定するための装置です。ASTM D1505 標準は、ガラスの熱膨張率を測定するための国際的な標準です。Cupwind は、ASTM D1505 標準に準拠した、ガラスの熱膨張率を測定するための装置です。ASTM D1505 標準は、ガラスの熱膨張率を測定するための国際的な標準です。



ASTM D1505 標準に準拠 Cupwind





00000000 0000 0000



□□□□□□□□ □□□□ □□□□



〇〇〇〇 〇〇〇〇〇〇 〇〇〇〇 〇〇〇〇 〇〇〇〇〇〇〇〇 〇〇〇〇〇〇〇〇

〇〇〇〇〇 〇〇〇〇〇〇〇〇 〇〇〇〇〇〇〇〇〇 〇〇〇〇〇〇〇 〇〇〇 〇〇〇〇〇〇〇〇 〇〇〇〇〇 〇〇〇〇〇〇〇〇〇 〇〇〇〇〇〇〇 〇〇〇〇〇 〇〇〇〇〇 〇〇〇〇
 〇〇〇〇〇 〇〇 〇〇〇〇〇〇〇 〇〇〇〇〇〇 〇〇 〇〇〇〇〇〇〇 〇〇〇〇〇 〇〇〇〇〇〇〇 〇〇〇〇〇〇〇 〇〇〇〇〇〇〇 〇〇〇〇〇〇〇 〇〇 〇〇〇〇〇〇〇
 〇〇〇〇 72/〇〇〇〇 48 〇〇 〇〇〇〇〇 〇〇 〇〇〇 〇〇〇〇〇〇〇.

〇〇〇 〇〇〇〇〇〇 〇〇〇〇〇 〇〇〇〇〇〇 〇〇〇〇〇〇〇〇〇 〇〇 〇〇〇〇〇〇〇〇 〇〇〇〇〇〇〇 〇〇〇〇 〇〇〇〇 〇〇〇 〇〇〇〇〇〇〇〇〇〇 〇〇〇〇〇〇〇〇〇
 〇〇〇〇〇〇〇 〇〇 〇〇〇〇〇〇〇 〇〇〇〇〇〇 〇〇〇〇 〇〇〇〇〇.



