

📄 8 📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄📄



📄📄📄📄

📄📄📄📄 10000 📄📄📄📄📄📄.

20 📄📄📄📄📄📄📄📄📄📄📄📄.

20 📄📄📄📄📄📄📄📄📄📄📄📄.

20 📄📄📄📄📄📄📄📄.

📄📄📄📄📄📄📄📄📄📄📄📄 Armani Zara 📄📄.









此报告为机密文件，仅供客户内部使用。未经客户书面许可，不得复制或向第三方泄露。如有违反，将依法追究法律责任。



TEST REPORT



0521087-0435
Page 3 of 4

SHENZHEN JIEFUMA TRADING CO., LTD
NO.415 RUNJIAN BUILDING, SHENZHEN ROAD,
HENGGAO, 518115, SHENZHEN, CHINA

LAB LOCATION: SHENZHEN
LAB NUMBER: 0521087-0435

ATTN: EMMA ZOU
CC: emma@bureauveritas.com

DATE IN: APR 07, 2021
MOD. LOG IN: /
DATE OUT: APR 13, 2021
REVISED DATE: /
WORKING DAYS: 5
PAGE: 2 OF 4

OVERALL RATING

PASS ☒
FAIL ☐
DATA ☐

TESTING FOR CA RS LEAD & CADMIUM ON NON-FOOD BEVERAGE GLASSWARE-EXTERIOR

Sample Description:	IRIDESCENT COATING CANDLE JAR	P.O. No.:	/
Manufacturer:	CUJWING COOPERATED FACILITY	Style:	/
Buyer:	IPSY	Country of Origin:	CHINA
Country of Origin:	CHINA	Country of Destination:	USA
Color:	IRIDESCENT	SKU Number:	ITEM# 8090
Brand name:	CUJWING III	Re-test:	Yes: ☐ No: ☒
Charge Vendor:	Yes: ☒ No: ☐	Previous Report No.:	17

EXECUTIVE SUMMARY:

Test content	Result Rating
CA RS Lead & Cadmium on non-food/beverage glassware-exterior	Meet Pass
Effectiveness of annealing ASTM F2175-20 Sec. 4.2 (NAF) With a tungsten carbide scriber, scratch twice around the inside knuckle of the article. Then scratch an "X" across the entire inside bottom surface of the article. At scratches are to be made using sufficient pressure to just penetrate the surface of the glass. Fill each article with water at the same room temperature as the glass. Wait 15 minutes, then empty the water and examine each piece for fractures. Shall show no fractures. Report the number of fractures, if any, for each test.	Pass
Thermal shock ASTM F2175-20 Sec. 4.2 (Mod) / ASTM C448 Modification: expanded scope to all other glass products in addition to candle containers. Shall not crack or break after tested per below: - prepare a cold-water bath at 21 ± 1.1°C (70 ± 2°F); - prepare a hot bath at 71 ± 1.1°C (160 ± 2°F); - immerse the sample completely in the hot water bath and allow to soak for 5 min ± 15 s; - transfer the sample to the cold bath; and - immerse for at least 30 s; - remove the sample from the cold bath and examine the sample for any cracking. Note: - the hot water that collects within the container during the first immersion shall be retained in the container through the second immersion; - the time of transfer from the hot bath to the cold bath shall be 15 ± 1 s; - Modification: sampling procedure not followed and expanded scope to all other glass products in addition to candle containers.	Pass

REMARK:

1. No enclosed protocol for test results in this report.



Wick Trimmer Cutter



Zinc Alloy Lid



Wooden Lid



Neck



Stopper



Reed

Gift Box.



Gift Box