

10000

20

20

20

Armani Zara



3000





[Cupwind 11](#)



[Cupwind 專業陶瓷杯 OEM 及 ODM](#)

[專業陶瓷杯、馬克杯、咖啡杯、茶杯、牛奶杯、啤酒杯、](#)

[各種陶瓷杯、馬克杯、咖啡杯、茶杯、牛奶杯、啤酒杯、](#)

[Cupwind 專業陶瓷杯、馬克杯、咖啡杯、茶杯、牛奶杯、啤酒杯、](#)



TEST REPORT



8521097-0435
Page 3 of 4

SHENZHEN JIERUMA TRADING CO., LTD
NO.415 RUNLIAN BUILDING, SHENZHU ROAD,
HENGGAO, 518115, SHENZHEN, CHINA

LAB LOCATION: SHENZHEN
LAB NUMBER: 8521097-0435

ATTN: EMMA ZOU
CC: emma@oupwind.com

DATE IN: APR 07, 2021
MOD. LOG IN: /
DATE OUT: APR 13, 2021
WORKING DAYS: 5
PAGE: 2 OF 4

OVERALL RATING

PASS ☒
FAIL ☐
DATA ☐

TESTING FOR CA 95 LEAD & CADMIUM ON NON-FOOD / BEVERAGE GLASSWARE-EXTERIOR

Sample Description:	IRIDESCENT COATING CANDLE JAR	P.O. No.:	
Manufacturer:	OUFWIND COOPERATED FACILITY	Style:	
Buyer:	PST	Country of Origin:	CHINA
Country of Origin:	CHINA	Country of Destination:	USA
Color:	IRIDESCENT	SKU Number:	ITEM# 8090
Brand name:	OUFWIND®	Re-test:	Yes: ☐ No: ☒
Charge Vendor:	Yes: ☒ No: ☐	Previous Report No.:	17

EXECUTIVE SUMMARY:


Test content	Result	Rating
CA 95 Lead & Cadmium on non-food/beverage glassware-exterior	Meet Pass	
Electron microscope of annealing	ASTM F2175-20 Sec. 4.2 (Mod) With a larger particle visible, scratch area around the inside knuckle of the article. Then scratch an "X" across the entire inside bottom surface of the article. All scratches are to be made using sufficient pressure to just penetrate the surface of the glass. Fill each article with water at the same room temperature as the glass. Wait 15 minutes, then empty the water and examine each piece for fractures. Shall show no fractures. Report the number of fractures, if any, for each test.	M PASS
Thermal shock	ASTM F2175-20 Sec. 4.2 (Mod) / ASTM C149 Modification: expanded scope to all other glass products in addition to candle containers. That not crack or break after tested per below: - prepare a hot bath at 71 ± 1.1°C (160 ± 2°F); - immerse the sample completely in the hot water bath and allow to soak for 1 min ± 15 s; - transfer the sample to the cold bath; and - immerse for at least 30 s; - remove the sample from the cold bath and examine the sample for any cracking. Note: - the hot water that collects within the container during the first immersion shall be retained in the container through the second immersion. the time of transfer from the hot bath to the cold bath shall be 15 ± 1 s. Modification: sampling procedure not followed and expanded scope to all other glass products in addition to candle containers.	M PASS

REMARK:

1. No enclosed protocol for test results in this report.

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

1



XXXXXX

