

第 11 章 数据库系统概论

10000个数据块

20个数据块

20个数据块

20个数据块

Armani Zara数据库系统

数据库 第 11 章 数据库系统概论



歡迎各界人士垂詢

歡迎各界人士垂詢 Cupwind 歡迎各界人士垂詢 OEM 及 ODM 服務

歡迎各界人士垂詢 3000 歡迎各界人士垂詢



歡迎各界人士垂詢 11oz 歡迎各界人士垂詢







Cupwind 專業 OEM 及 ODM

□ □

1111111111

Cupwind 0000000000000000 c .



TEST REPORT



8521097-0435
Page 3 of 4

SHENZHEN JIERUMA TRADING CO., LTD.
NO.415 RUNLIAN BUILDING, SHENZHU ROAD,
HENGGAO, 518115, SHENZHEN, CHINA

LAB LOCATION: SHENZHEN
LAB NUMBER: 8521097-0435

ATTN: EMMA ZOU
CC: emma@oupwind.com

DATE IN: APR 07, 2021
MOD. LOG IN: /
DATE OUT: APR 13, 2021
REVISED DATE: /
WORKING DAYS: 5
PAGE: 2 OF 4

OVERALL RATING	
PASS	☒
FAIL	☐
DATA	☐

TESTING FOR CA 95 LEAD & CADMIUM ON NON-FOOD / BEVERAGE GLASSWARE-EXTERIOR

Sample Description:	IRIDESCENT COATING CANDLE JAR
Manufacturer:	OUFWIND COOPERATED FACILITY
Buyer:	POST
Country of Origin:	CHINA
Country of Destination:	USA
Color:	IRIDESCENT
Brand name:	OUFWIND IS
Re-test:	Yes: ☐ No: ☒
Charge Vendor:	Yes: ☒ No: ☐
Previous Report No.:	17

EXECUTIVE SUMMARY:


Test content		Result Rating	Test Pass	
CA 95 Lead & Cadmium on non-food/beverage glassware-exterior				
Electronance of annealing	ASTM F2175-20 Sec. 4.2 (Mod)	With a tungsten carbide needle, scratch twice around the inside knuckle of the article. Then scratch an "X" across the entire inside bottom surface of the article. All scratches are to be made using sufficient pressure to just penetrate the surface of the glass. Fill each article with water at the same room temperature as the glass. Wait 15 minutes, then empty the water and examine each piece for fractures. Shall show no fractures. Report the number of fractures, if any, for each	M	PASS
Thermal shock	ASTM F2175-20 Sec. 4.2 (Mod) / ASTM C149	Modification: expanded scope to all other glass products in addition to candle containers. That not crack or break after tested per below: - Small not crack or break after tested per below: - prepare a cold water bath at 11 ± 1.1°C (50 ± 2°F); - prepare a hot bath at 71 ± 1.1°C (160 ± 2°F); - immerse the sample completely in the hot water bath and allow to soak for 1 min ± 15 s; - transfer the sample to the cold bath; and - immerse for at least 30 s; - remove the sample from the cold bath and examine the sample for any cracking. Note: - the hot water that collects within the container during the first immersion shall be retained in the container through the second immersion. The time of transfer from the hot bath to the cold bath shall be 15 ± 1 s. Modification: sampling procedure not followed and expanded scope to all other glass products in addition to candle containers.	M	PASS

REMARK:

1. No enclosed protocol for test results in this report.

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

XXXXXXXXXXXXXXXXXXXXXXXXXXXX .



XXXX

