

□

□□□□□□

A□ 10000□□□□□□□□

20□□□□□□□□

20□□□□□□

20□□□□□□□□

Armani Zara□□□□□□□□

□□□□□□□□ □□□□□□□□□□ □□□□□

□□□□



Cupwind 是 OEM/ODM 廠商

□□□□□□□□□□□□□□□□/□□□□□□□□



TEST REPORT



Page 3 of 4

MOJIS BUILDING, SHENZU FOME, CHINA

LAB LOCATION: SHENZHEN
LAB NUMBER: (852) 1097-0435

Call 65 Pro

ATTN: EMMA ZOU
Cali 65

DATE IN: APR 11, 2024
MOD. LOG: 1
DATE OUT: APR 11, 2024
REVISED DATE: /
WORKING DAYS: 5
PAGE: 2 OF 4

OVERALL RATING

PASS	<u> X </u>
FAIL	<u> </u>
DATA	<u> </u>

TESTING FOR
CA 65 LEAD & CADMIUM ON NON-FOOD
BEVERAGE GLASSWARE-EXTERIOR

Sample Description:		DESICCANT COATING CANDLE JAR		Part No.:	
Ind	10000				
Buyer:	QPSV	Origin:	USA		
Country of Origin:	CHINA	Country of Destination:	USA		
Color:	DESICCANT	SKU Number:	ITEM# 8090		
Brand name:	CLAWING II				
Yes:	No: X	Change Vendor:	Yes: X	No:	
Phenolphthalein No.:					

EXECUTIVE SUMMARY:

Test Content		Result/Rating	
Cast, Seal & Cautrain on non-toothed gaskets enter		Moist Pass	
Efficiency of sealing 	ASTM F1979-10 Sec. 4.2 (NA)	With a tapered needle probe, touch the surface around the inside cracks of the gasket. Then press at 20° angle to the surface to make the surface of the article. All scratches are to be made using applied pressure to just penetrate the surface of the glass. The article with water at the same room temperature as the glass. Wait 15 minutes. Then empty the water and examine each piece for fractures. Seal show no fractures. Report the number of fractures, if any, for each.	M PASS
Thermal shock 	ASTM F1979-10 Sec. 4.2 (NA) ASTM C44	Modification: expanded scope to all other glass products in addition to candle containers. Small test pieces or sample after tested per below procedure. The hot water bath is at 175 ± 2° F ± 2° F. Immerse the sample at 275 ± 1° F (150 ± 2° F) submerged the sample for 1 min ± 1 s. The hot water bath and allow to soak for 1 min ± 1 s. Transfer the sample to the cold water bath, and immerse for at least 30 s. Remove the sample from the cold bath and examine the sample for any cracking. The hot water that collects within the container during the first immersion shall be retained in the container through the second immersion. The time of transfer from the hot bath to the cold bath shall be 15 ± 1 s. Modification: sampling procedure not followed and expanded scope to all other glass products in addition to candle containers.	M PASS

REMARK.

1. Full worksheet produced for test results in this report.

Cupwind 10000

20□□□□□□□□

20□□□□□□

20□□□□□□□□□□□□□□□□

