

1

陶瓷罐

A 10000个陶瓷罐

20个陶瓷罐

20个陶瓷罐

20个陶瓷罐

Armani Zara 陶瓷罐

陶瓷罐 OEM ODM



陶瓷罐

● 歡迎各界人士來電洽詢 Cupwind 專業承接各類陶瓷 OEM 及 ODM 業務 價格公道 品質優良 歡迎垂詢

● 承接各類陶瓷產品設計及生產

● 歡迎各界人士來電洽詢 CMYK 印刷

● 承接各類陶瓷產品設計及生產 500 件起 價格公道 品質優良 歡迎垂詢

● Cupwind 專業承接各類陶瓷 OEM 及 ODM 業務 價格公道 品質優良 歡迎垂詢

● 承接各類陶瓷產品設計及生產 10 件起 價格公道 品質優良 歡迎垂詢



0000000000000000/00000000



Call 65 Pro 

DATE IN: APR 11, 2024
MOD. LOG: 1
DATE OUT: APR 11, 2024
REVISED DATE: /
WORKING DAYS: 5
PAGE: 2 OF 4

OVERALL RATING

PASS	<u> X </u>
FAIL	<u> </u>
DATA	<u> </u>

TESTING FOR
CA 65 LEAD & CADMIUM ON NON-FOOD /
BEVERAGE GLASSWARE-EXTERIOR

Sample Description: DESICCANT COATING CANDLE JAR		Part No.:	
Ind	10000		
Buyer:	GRV	Ship:	USA
Country of Origin:	CHINA	Country of Destination:	USA
Color:	DESICCANT	SKU Number:	ITEM# 8090
Brand name:	CLAWING II		
Yes:	No: X	Change Vendor:	Yes: X No:
Phenolphthalein No.:			

EXECUTIVE SUMMARY

Test content			Result Rating	
CA 8.1 Seal & Cauldron on non-food/beverage glassware exterior			Moist Pass	
Efficiency of erasing	ASTM F2759-12 Sec. 4.2 (MoS)	With a tungsten carbide scrubber, scrub the area around the inside cracks of the spout. Then scrub the area around the inside cracks made on the surface of the glass. All scratches are to be made using sufficient pressure to just penetrate the surface of the glass. Then scrub the area with water at the same room temperature as the glass. Wait 10 minutes, then inspect the water and examine each piece for fractures. Seal show no fractures. Report the number of fractures, if any, for each.	M	Pass
Thermal shock	ASTM F2759-12 Sec. 4.2 (MoS) ASTM C54	Modification: expanded scope to all other glass products in addition to beverage containers. 1. Heat test pieces or test bath at $175 \pm 2^\circ\text{F}$. 2. Immerse the test bath at $27 \pm 1^\circ\text{C}$ ($80 \pm 2^\circ\text{F}$) immediately in the hot water bath and in the hot water bath and allow to soak for at least 10 s. 3. Transfer the sample to the cold water bath, and immerse for at least 30 s. 4. Remove the sample from the cold bath and examine the sample for any cracking. 5. The hot water that collects within the container during the first immersion shall be retained in the container through the second immersion. 6. The time of transfer from the hot bath to the cold bath shall be 10 s. 7. Modification: sampling procedure not followed and expanded scope to all other glass products in addition to beverage containers.	M	Pass

REMARK.

4. Full services provided for test results in this report:

Cupwind 10000

20□□□□□□□□

20□□□□□

20

