



A 10000

20

20

20

Armani Zara

11

000000 000000 000000000000 12 0000000
 0000000000000000000000
 000000000000

3M616
 30000 2000
 30000

Cupwind 玻璃 OEM/ODM 玻璃器皿

玻璃器皿/玻璃器皿

玻璃器皿/玻璃器皿



Wick Trimmer/Cutter

Zinc Alloy Lid

Wooden Lid



TEST REPORT



0521087-0435
Page 3 of 4

SHENZHEN JIERUMA TRADING CO., LTD.
NO.415 RUNLIAN BUILDING, SHENZHU ROAD,
HENGGAO, 518115, SHENZHEN, CHINA

LAB LOCATION: SHENZHEN
LAB NUMBER: 0521087-0435

CC: anna@cupwind.com

DATE IN: APR 07, 2021
MOD. LOG IN: APR 13, 2021
DATE OUT: APR 13, 2021
REVISION: 2 OF 1

OVERALL RATING

PASS ☒
FAIL ☐
DATA ☐

TESTING FOR CASS LEAD & CADMIUM ON NON-FOOD BEVERAGE GLASSWARE-EXTERIOR

Sample Description:	IRIDESCENT COATING CANDLE JAR
Manufacturer:	CUPWIND COOPERATED
Buyer:	IPSY
Country of Origin:	CHINA
Color:	IRIDESCENT
Brand name:	CUPWIND B
Re-test:	Yes: ☐ No: ☒
Previous Report No.:	7
P.O. No.:	
Country of Destination:	USA
SKU Number:	ITEM: 8090
Change Vendor:	Yes: ☒ No: ☐

EXECUTIVE SUMMARY:

Test content	Result Rating
CA 66 Lead & Cadmium on non-food/beverage glassware-exterior	Most Pass

Effectiveness of annealing	ASTM F2175-20 Sec. 4.2 (NA6)	With a tungsten carbide scriber, scratch twice around the inside knuckle of the article. Then scratch an "X" across the entire inside bottom surface of the article. All scratches are to be made using sufficient pressure to just penetrate the surface of the glass. Fill each article with water at the same room temperature as the glass. Soak 15 minutes, then empty the water and examine each piece for fractures. Show no fractures. Report the number of fractures, if any, for each test.	M	PASS
Thermal shock	ASTM F2175-20 Sec. 4.2 (NA6) + ASTM C149	Modification: expanded scope to all other glass products in addition to candle containers. Shall not crack or break after tested per below: - prepare a cold-water bath at 21 ± 1 °C (70 ± 2 °F); - prepare a hot bath at 71 ± 1 °C (160 ± 2 °F); - submerge the sample completely in the hot water bath and allow to soak for 5 min ± 15 s; - transfer the sample to the cold bath, and immerse for at least 30 s; - remove the sample from the cold bath and examine the sample for any cracking. Note: - the hot water that collects within the container during the first immersion shall be retained in the container through the second immersion. - the time of transfer from the hot bath to the cold bath shall be 15 ± 1 s. Modification: sampling procedure not followed and expanded scope to all other glass products in addition to candle containers.	M	PASS

REMARK:

1. No enclosed protocol for test results in this report.

Cupwind 玻璃 10000 玻璃器皿

20 玻璃器皿

20

20

