



A 10000□□□□□□□□

20□□□□□□□□

20□□□□□□

20□□□□□□□□

Armani Zara□□□□□□□□

□□□□□□ □□□□□□□□□□ □□□□□□

14oz

Nest Fragrance Baobab Collection





Cupwind OEM/ODM

XXXXXXXXXXXXXXXXXXXX/XXXXXXXXXX

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX



Wick Trimmer Cutter

Zinc Alloy Lid

Wooden Lid



TEST REPORT



9821097-0426
Page 3 of 4

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

LAB LOCATION: SHENZHEN
LAB NUMBER: 9821097-0435

XXXXXXXXXX Call 65 Pro XXXXASTMXXXXXXXXXXXXXXXXXXXXXXXXXXXX

ATTN: EMMA ZOU
DATE: APR 19, 2023
REVISED DATE: /
WORKING DAYS: 5
PAGE: 2 OF 4

OVERALL RATING	
PASS	X
FAIL	
DATA	

TESTING FOR CA 65 LEAD & CADMIUM ON NON-FOOD / BEVERAGE GLASSWARE-EXTERIOR

Sample Description:	IRIDESCENT COATING CANDLE JAR		
Buyer:	POY	Country of Origin:	CHINA
Country of Origin:	CHINA	Country of Destination:	USA
Color:	IRIDESCENT	SKU Number:	10AMF 8090
Brand name:	CUPWIND®		
Re-test:	Yes: <input type="checkbox"/>	No: <input checked="" type="checkbox"/>	Change Vendor: Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>
Previous Report No.:	/		

EXECUTIVE SUMMARY:

Test content	Result Rating	Method
Ca 65 Lead & Cadmium on non-food/beverage glassware-exterior		
Dimensions of article: ASTM F2175-20 Sec. 4.2 (Mold) Method: With a longpen ballpoint pen, scratch twice around the inside lip/edge of the article. Then scratch an "X" across the entire inside bottom surface of the article. All scratches are to be made using sufficient pressure to just penetrate the surface of the glass. Fill each article with water at the same room temperature as the glass. Wait 15 minutes, then empty the water and examine each piece for fractures. Do not show no fractures. Report the number of fractures, if any, for each test.	M	PASS
Thermal shock: ASTM F2175-20 Sec. 4.2 (Mold / ASTM C149) Modification: expanded scope to all other glass products in addition to candle containers. Note: Do not stack or break after tested per section - prepare a cold water bath at 21± 1.1°C (70 ± 2°F); - prepare a hot bath at 71 ± 1.1°C (160 ± 2°F); - immerse the sample completely in the hot water bath and allow to soak for 5 min ± 15 s; - transfer the sample to the cold bath and immerse for at least 30 s; - remove the sample from the cold bath and examine the sample for any cracking.	M	PASS

REMARK:
1. No enclosed protocol for test results in this report.

Cupwind 10000XXXXXXXXXXXXXXXXXXXX

20XXXXXXXXXXXX

20XXXXXX

20XXXXXXXXXXXXXXXXXXXXXXXXXXXX

