



A 10000

20

20

20

Armani Zara

Cupwind

1111

00000000 13 0000000000 100 00

0000000000 00000000

00000000000000000000



Capurind

00000000 13 0000000000 100 00

0000000000 00000000

00000000000000000000



Capurind

00000000 13 0000000000 100 00

0000000000 00000000

00000000000000000000



Capurind

Cupwind 杯 OEM/ODM 玻璃杯

玻璃杯/玻璃杯

玻璃杯/玻璃杯



Wick Trimmer Cutter



Zinc Alloy Lid



Wooden Lid



TEST REPORT



8521087-0435
Page 3 of 4

SHENZHEN JIERUMA TRADING CO., LTD
NO.415 RUNLIAN BUILDING, SHENZHEN ROAD,
HENGGAO, 518115, SHENZHEN, CHINA

LAB LOCATION: SHENZHEN
LAB NUMBER: 8521087-0435

CC: anna@cupwind.com

DATE IN: APR 07, 2021
MOD. LOG IN: APR 13, 2021
DATE OUT: APR 13, 2021
REVISION: 2 OF 1

OVERALL RATING

PASS ☒
FAIL ☐
DATA ☐

TESTING FOR CASS LEAD & CADMIUM ON NON-FOOD BEVERAGE GLASSWARE-EXTERIOR

Sample Description:	IRIDESCENT COATING CANDLE JAR
Manufacturer:	CUPWIND COOPERATED
Buyer:	IPSY
Country of Origin:	CHINA
Color:	IRIDESCENT
Brand name:	CUPWIND B
Re-test:	Yes: ☐ No: ☒
Previous Report No.:	7

EXECUTIVE SUMMARY:

Test content	Result Rating
CA 66 Lead & Cadmium on non-food/beverage glassware-exterior	Meet Pass

Effectiveness of annealing	ASTM F2175-20 Sec. 4.2 (NA6)	With a tungsten carbide scriber, scratch twice around the made knuckle of the article. Then scratch an "X" across the entire inside bottom surface of the article. All scratches are to be made using sufficient pressure to just penetrate the surface of the glass. Fill each article with water at the same room temperature as the glass. Wait 15 minutes, then empty the water and examine each piece for fractures. Show no fractures. Report the number of fractures, if any, for each test.	M	PASS
Thermal shock	ASTM F2175-20 Sec. 4.2 (NA6) + ASTM C149	Modification: expanded scope to all other glass products in addition to candle containers. Shall not crack or break after tested per below: - prepare a cold-water bath at 21 ± 1 °C (70 ± 2 °F); - immerse the sample completely in the hot water bath and allow to soak for 5 min ± 15 s; - transfer the sample to the cold bath, and immerse for at least 30 s; - remove the sample from the cold bath and examine the sample for any cracking. Note: - the hot water that collects within the container during the first immersion shall be retained in the container through the second immersion; - the time of transfer from the hot bath to the cold bath shall be 15 ± 1 s. Modification: sampling procedure not followed and expanded scope to all other glass products in addition to candle containers.	M	PASS

REMARK:

1. No enclosed protocol for test results in this report.

Cupwind 杯 10000 玻璃杯

20 玻璃杯

20□□□□□□

20□□□□□□□□□□□□□□□□

