

Ombre Sprays 300



300

10000

20

20

20

Armani Zara

300

[illegible]

□ □





Cupwind ODM/OEM



Cupwind 專業生產 OEM 及 ODM

各種規格、顏色、圖案、尺寸、數量均可承接

歡迎垂詢、洽談、合作

[Cupwind 專業生產各種金屬製品](#) .



TEST REPORT



8521097-0435
Page 3 of 4

SHENZHEN JIERUMA TRADING CO., LTD
NO.415 RUNLIAN BUILDING, SHENZHEN ROAD,
HENGGAO, 518115, SHENZHEN, CHINA

LAB LOCATION: SHENZHEN
LAB NUMBER: 8521097-0435

ATTN: EMMA ZOU
CC: emma@cupwind.com

DATE IN: APR 07, 2021
MOD. LOG IN: /
DATE OUT: APR 13, 2021
REVISD DATE: /
WORKING DAYS: 5
PAGE: 2 OF 4

OVERALL RATING	
PASS	☒
FAIL	☐
DATA	☐

TESTING FOR CA 95 LEAD & CADMIUM ON NON-FOOD / BEVERAGE GLASSWARE-EXTERIOR

Sample Description:	IRIDESCENT COATING CANDLE JAR		
Manufacturer:	CUPWIND COOPERATED FACILITY	P.O. No.:	
Buyer:	PST	Style:	
Country of Origin:	CHINA	Country of Destination:	USA
Color:	IRIDESCENT	SKU Number:	ITEM: 8090
Brand name:	CUPWIND IS		
Re-test:	Yes: ☐ No: ☒	Charge Vendor:	Yes: ☒ No: ☐
Previous Report No.:	17		

EXECUTIVE SUMMARY:

Test content	Result Rating	Meet Pass
CA 95 Lead & Cadmium on non-food/beverage glassware-exterior		
Electron microscope of annealing	ASTM F2175-20 Sec. 4.2 (Mod)	M PASS
Thermal shock	ASTM F2175-20 Sec. 4.2 (Mod) / ASTM C149	M PASS

With a larger particle size, scratch area around the inside knuckle of the article. Then scratch on "X" across the entire inside bottom surface of the article. All scratches are to be made using sufficient pressure to just penetrate the surface of the glass. Fill each article with water at the same room temperature as the glass. Wait 15 minutes, then empty the water and examine each piece for fractures. Shall show no fractures. Report the number of fractures, if any, for each test.

Modification: expanded scope to all other glass products in addition to candle containers.

Test not crack or break after tested per below:

- prepare a hot water bath at $71 \pm 1.1^{\circ}\text{C}$ ($160 \pm 2^{\circ}\text{F}$);
- immerse the sample completely in the hot water bath and allow to soak for $1 \text{ min} \pm 15 \text{ s}$;
- transfer the sample to the cold bath; and
- immerse for at least 30 s;
- remove the sample from the cold bath and examine the sample for any cracking.

Note:


- the hot water that collects within the container during the first immersion shall be retained in the container through the second immersion; the time of transfer from the hot bath to the cold bath shall be $15 \pm 1 \text{ s}$.

Modification: sampling procedure not followed and expanded scope to all other glass products in addition to candle containers.

REMARK:

1. No enclosed protocol for test results in this report.

XXXXXXXXXXXXXXXXXXXXXXXXXXXX



XXXXXX

XXXXXXXXXXXX

XXXXXXXX opp XXXXXXXX24 1/48 1/72 1/144 XXXXXXXXXXXXXXXX

XX



Cupwind