

☐ OEM
 ☐ ODM



本公司為Cupwind 原廠OEM 廠, 專營, 專營
 本公司為Cupwind 原廠OEM 廠, 專營, 專營

□□□□□ CMYK □□□□□

500

□□□□□ 10 □□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□/□□□□□□□□



Page 3 of 4

[illegible]

LAB LOCATION: SHENZHEN
LAB NUMBER: 085211017-0435

Call 65 Pro

ATTN: EMMA ZOU
6165

DATE IN: 04/01/2004
MOD. LOG: 1
DATE OUT: 04/01/2004
REVISED DATE: 04/01/2004
WORKING DAYS: 5
PAGE: 2 OF 4

OVERALL RATING

PASS	<u> X </u>
FAIL	<u> </u>
DATA	<u> </u>

TESTING FOR
CA 65 LEAD & CADMIUM ON NON-FOOD
BEVERAGE GLASSWARE-EXTERIOR

Sample Description: DESICENT COATING CANDLE JAR									
Ind 10000									
Buyer:	Q35V	Order No.:							
Country of Origin:	CHINA	Country of Destination:	USA						
Color:	PURPLE/SCENT	SKU Number:	TRIMAR 8090						
Brand name:	CUSWING III								
Pre-test:	Yes: ☐ No: ☒	Change Vendor:	Yes: ☒ No: ☐						
Low Backout No.									

EXECUTIVE SUMMARY

Test content		Result Rating
CAI Seal & Coldman in non-food/beverage glassware container		Master Pass
Disinfectant (if available) ASTM F2799-05 Sec. 4.2 (N/A)	Fill a large clean, sterile bottle, bottle open from the inside (ready to use) of the article. Then, scratch on "1" across the entire inside bottom surface of the article. All inside marks are to be made using sufficient pressure to just penetrate the surface of the glass. Fill the article with water at the same room temperature as the glass. Wait 15 minutes, then empty the water and examine each piece for fractures. Seal; show no fractures. Report the number of fractures, if any, for each.	M PASS
Thermal shock ASTM F2799-05 Sec. 4.2 (N/A) ASTM C568	Modification: -exposed; expose to all other glass products in addition to candle containers. Small test cracks or break after tested per below Prepare a cold bath at 15 ± 1 °F (-1 ± 0.5 °C) ± 2 °F. Prepare a hot bath at 275 ± 1 °F (140 ± 0.5 °F) immerse the sample completely in the hot water bath and allow to soak for 3 min ± 15 s. Transfer the sample to the cold bath, and immerse for at least 30 s. Remove the sample from the cold bath and examine the sample for any cracking. the hot water that collects within the container during the first immersion shall be retained in the container through the first immersion. the loss of liquid from the hot bath to the cold bath shall be 15 ± 5 Medium test: - sampling procedure not followed and expanded scope to all other glass products in addition to candle containers.	M PASS

THE MAIN RESULT

1. Full enclosed provided the test results in this report

Cupwind 10000

20□□□□□□□□

20□□□□□□

20□□□□□□□□□□□□□□□□□□

