

2022年7月



1

2022年7月

A 10000

20

20

20

Armani Zava

2022年7月

2022年7月

7 30000



Cupwind 〇〇 OEM/ODM 〇〇〇〇〇

□□□□□□□□□□□□□□/□□□□□□□□

□ □



Wick Trimmer Cutter



Zinc Alloy Lid



Wooden Lid



TEST REPORT



Page 3 of 4

SHENZHEN JIERUMA TRADING CO., LTD
NO.415 RUNLIAN BUILDING, SHENZHU ROAD
HONGKANG, 518115, SHENZHEN, CHINA

LAB LOCATION: SHENZHEN
LAB NUMBER: (852) 3087-0435

ATTN: EMMA ZOU
CC: emma@supwind.com

DATE IN: APR 07, 2023
MOD. LOG IN: /
DATE OUT: APR 13, 2023
REVISED DATE: 5
WORKING DAYS: 2 OF 4

Cali 65

Call 03

OVERALL RATING:

PASS	<u> X </u>
FAIL	<u> </u>
DATA	<u> </u>

FOR

TESTING FOR
CA 65 LEAD & CADMIUM ON NON-FOOD
BEVERAGE GLASSWARE-EXTERIOR

Sample Description:		DESICCANT COATING CANXLE JAR	
Manufacturer:	CUPWARD COOPERATED	P.O. No.:	
	FACTORY		
Buyer:	IPSY	Style:	
Country of Origin:	CHINA	Country of Destination:	USA
Color:	DESICCANT	SKU Number:	TRIMR 2090
Ind. No. 10000		Lot No. 0000000000	Quality Number: Yes: ☒ No: ☐
Previous Report No.			

EXECUTIVE SUMMARY:

Test content		Result/Rating	
CA 161 and CA160 on non-food/beverage glassware surface		Moist Pass	
Disinfectant resistance	ASTM F2179-93 Sec. 4.2 (MNE)	With a hydrogen peroxide sprayer, sprayer once around the inside knuckle of the article. Then sprayer "X" across the inside knuckle article and surface of the article. All sprayers are to be made using sufficient pressure to just penetrate the surface of the glass. Then fill article with water at the same room temperature as the glass. Wait 15 minutes. Then empty the water and examine each piece for fractures. Mark also any fractures. Report the number of fractures, if any, for each.	M PASS
Thermal shock	ASTM F2179-93 Sec. 4.2 (MNE) ASTM C163	Modification: expanded scope to all other glass products in addition to beverage containers. Shut cold water on cold water until tested per below (change a cold water temperature to 15 ± 1°F (-1 ± 2°)). Remove a hot bath at 217 ± 1°F (100 ± 2°) (increase the sample complexity in the hot water bath and allow to soak for 15 min ± 10 s). Transfer the sample to the cold bath and immerse for at least 30 s. Remove the sample, let the cold bath and examine the sample for any cracking. Note: The hot water that collects within the container during the first immersion shall be retained in the container through the second immersion. The time of transfer from the hot bath to the cold bath shall for 15 ± 1 s. Modification: expanded scope to all other glass products in addition to beverage containers.	M PASS

REMARK:

1. Has enclosed provided the test results in this report

Cupwind 10000

20□□□□□□□□

20□□□□□

20

