

El lujo adorna la botella del difusor de cristal de láminas de 200 ml



El vidrio difusor puede rociar diferentes colores Pantone, lo que lo hace combinar bien con diferentes diseños de vidrio para velas y aromas de fragancias. Es perfecto para decoración del hogar, aromaterapia, spa, meditación, baño.




Este difusor con diseño de acuarela hecho a mano, tiene un diseño de velas a juego. Es un producto de decoración del hogar muy bueno para los clientes. La botella difusora de vidrio vacía también es un buen jarrón para flores, simple y clásico.



Cupwind es uno de los más profesionales. [Fabricante de botellas difusoras de vidrio de caña de China](#). Tenemos nuestro propio taller de decoración para controlar la calidad de la botella del difusor de varillas antes de su envío.











Cupwind también ofrece otros accesorios relacionados con la botella difusora de carrizo, como caña, tapón, caja de regalo, tapón, etc.

Contamos con 6 socios cooperativos estables desde hace años. La calidad combina perfectamente con nuestros portavelas.



Accessories That Related

With requests of our customers, Cupwind also offers accessories such as gift box for scented candles, wick tool set like wick trimmer, cutter, snuffer, lids in wood and metal like stainless steel and zinc alloy.



Zinc Alloy Lid

Wick Trimmer Cutter



Wooden Lid

Tin metal lid



Glass Lid

Stopper



Neck

Reed



Gift Box

Gift Box



También ofrecemos cajas de regalo OEM y ODM para botellas de difusor de láminas. Si no es necesaria la caja de regalo, la forma común que utilizamos es envolver cada botella difusora de vidrio en una bolsa de opp para mantenerla alejada del polvo. Cajas de cartón corrugado con divisores transversales. La plataforma de madera siempre es eficiente durante el transporte. Y agregaremos una red de algodón en el lugar de la puerta para protegerla de caídas al abrir la puerta del contenedor.



Todos nuestros pedidos de vidrio son probados por un tercero. Por lo general, optamos por las pruebas Cali 65 Pro, pruebas ASTM (recocido y choque térmico), pruebas de plomo y cadmio.



TEST REPORT



(8521)097-0435
Page 3 of 4

SHENZHEN JIERUMA TRADING CO., LTD
NO.415 RUNLIAN BUILDING, SHENZHU ROAD,
HENGGAANG, 518115, SHENZHEN, CHINA

LAB LOCATION: SHENZHEN
LAB NUMBER: (8521)097-0435

ATTN: EMMA ZOU
CC: emma@cupwind.com

DATE IN: APR 07, 2021
MOD. LOG IN: /
DATE OUT: APR 13, 2021
REVISED DATE: /
WORKING DAYS: 5
PAGE: 2 OF 4

OVERALL RATING

PASS ☒
FAIL ☐
DATA ☐

TESTING FOR CA 65 LEAD & CADMIUM ON NON-FOOD / BEVERAGE GLASSWARE-EXTERIOR

Sample Description:	IRIDESCENT COATING CANDLE JAR		
Manufacturer:	CUPWIND COOPERATED FACILITY	P.O. No.:	/
Buyer:	IPSY	Style:	/
Country of Origin:	CHINA	Country of Destination:	USA
Color:	IRIDESCENT	SKU Number:	ITEM# 8090
Brand name:	CUPWIND®		
Re-test:	Yes: ☐ No: ☒	Charge Vendor:	Yes: ☒ No: ☐
Previous Report No.:	/		

EXECUTIVE SUMMARY:

Test content		Result/Rating	
CA 65 Lead & Cadmium on non-food/beverage glassware-exterior		Meet/Pass	
Effectiveness of annealing	ASTM F2179-20 Sec. 4.2 (Mod)	With a tungsten carbide scribe, scratch once around the inside knuckle of the article. Then scratch an "X" across the entire inside bottom surface of the article. All scratches are to be made using sufficient pressure to just penetrate the surface of the glass. Fill each article with water at the same room temperature as the glass. Wait 15 minutes, then empty the water and examine each piece for fractures. Shall show no fractures. Report the number of fractures, if any, for each test. Modification: expanded scope to all other glass products in addition to candle containers.	M PASS
Thermal shock	ASTM F2179-20 Sec. 4.2 (Mod) / ASTM C149	Shall not crack or break after tested per below - prepare a cold-water bath at 21±1.1°C (70±2°F). - prepare a hot bath at 71±1.1°C (160±2°F) - immerse the sample completely in the hot water bath and allow to soak for 5 min ± 10 s. - transfer the sample to the cold bath, and immerse for at least 30 s. - remove the sample from the cold bath and examine the sample for any cracking. Note: - the hot water that collects within the container during the first immersion shall be retained in the container through the second immersion - the time of transfer from the hot bath to the cold bath shall be 15 ± 1 s Modification: sampling procedure not followed and expanded scope to all other glass products in addition to candle containers.	M PASS

REMARK:

- No enclosed protocol for test results in this report.