

## **Botella difusora de vidrio de caña con patrón de rayas de nuevo diseño, 6 oz**



El vidrio transparente es capaz de rociar diferentes colores Pantone, lo que hace que combine bien con diferentes diseños de vidrio para velas y fragancias. Es perfecto para la decoración del hogar, aromaterapia, spa, meditación, baño.



Esta botella con diseño de rayas es un diseño popular, hay un diseño de tarro de vela a juego para ella. Es un producto de decoración del hogar que combina muy bien con los clientes. La botella difusora de vidrio vacía también es un buen jarrón para flores, simple y clásico.



Cupwind es uno de los más profesionales. [Fabricante de botella de difusor de vidrio de rayas de China](#). Tenemos nuestro propio taller de decoración para vigilar la calidad de la botella difusora de caña antes de enviarla.

El MOQ de esta botella difusora de forma especial es de 30,000 piezas.









Cupwind también ofrece otros accesorios relacionados con la botella difusora de caña, como caña, enchufe, caja de regalo, tapón, etc.

Tenemos 6 socios cooperativos estables durante años. La calidad es una gran combinación con nuestros portavelas.



## Accessories That Related

With requests of our customers, Cupwind also offers accessories such as gift box for scented candles, wick tool set like wick trimmer, cutter, snuffer, lids in wood and metal like stainless steel and zinc alloy.



Zinc Alloy Lid

Wick Trimmer Cutter



Wooden Lid

Tin metal lid



Glass Lid

Stopper



Neck

Reed



Gift Box

Gift Box



También ofrecemos cajas de regalo OEM y ODM para botellas difusoras de caña. Si la caja de regalo no es necesaria, la forma común que usamos es envolver cada botella difusora de vidrio en una bolsa de opp para evitar el polvo. cajas de cartón corrugado con divisores transversales. El palé de madera siempre es eficiente durante el transporte, y agregaremos una red de algodón en el lugar de la puerta para protegerlo de caídas al abrir la puerta del contenedor.



Todos nuestros pedidos de vidrio son probados por un tercero. Por lo general, utilizamos pruebas Cali 65 Pro, pruebas ASTM (recocido y choque térmico), pruebas de plomo y cadmio.



## TEST REPORT



(8521)097-0435  
Page 3 of 4

SHENZHEN JIERUMA TRADING CO., LTD  
NO.415 RUNLIAN BUILDING, SHENZHU ROAD,  
HENGANG, 518115, SHENZHEN, CHINA

LAB LOCATION: SHENZHEN  
LAB NUMBER: (8521)097-0435

ATTN: EMMA ZOU  
CC: emma@cupwind.com

DATE IN: APR 07, 2021  
MOD. LOG IN: /  
DATE OUT: APR 13, 2021  
REVISED DATE: /  
WORKING DAYS: 5  
PAGE: 2 OF 4

### OVERALL RATING

PASS ☒ X  
FAIL ☐  
DATA ☐

TESTING FOR  
CA 65 LEAD & CADMIUM ON NON-FOOD /  
BEVERAGE GLASSWARE-EXTERIOR

|                      |                                                                       |                         |                                                                       |
|----------------------|-----------------------------------------------------------------------|-------------------------|-----------------------------------------------------------------------|
| Sample Description:  | IRIDESCENT COATING CANDLE JAR                                         |                         |                                                                       |
| Manufacturer:        | CUPWIND COOPERATED FACILITY                                           | P.O. No.:               | /                                                                     |
| Buyer:               | IPSY                                                                  | Style:                  | /                                                                     |
| Country of Origin:   | CHINA                                                                 | Country of Destination: | USA                                                                   |
| Color:               | IRIDESCENT                                                            | SKU Number:             | ITEMF: 8090                                                           |
| Brand name:          | CUPWIND 6                                                             |                         |                                                                       |
| Re-test:             | Yes: <input type="checkbox"/> No: <input checked="" type="checkbox"/> | Charge Vendor:          | Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/> |
| Previous Report No.: | /                                                                     |                         |                                                                       |

### EXECUTIVE SUMMARY:

| Test content                                                 |                                          | Result/Rating                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |        |
|--------------------------------------------------------------|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| CA 65 Lead & Cadmium on non-food/beverage glassware-exterior |                                          | Meet/Pass                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |        |
| Effectiveness of annealing                                   | ASTM F2179-20 Sec. 4.2 (Mod)             | With a tungsten carbide scribe, scratch once around the inside knuckle of the article. Then scratch an "X" across the entire inside bottom surface of the article. All scratches are to be made using sufficient pressure to just penetrate the surface of the glass. Fill each article with water at the same room temperature as the glass. Wait 15 minutes, then empty the water and examine each piece for fractures. Shall show no fractures. Report the number of fractures, if any, for each test.                                                                                                                                                                                                                                                                                                                                                                                                    | M PASS |
| Thermal shock                                                | ASTM F2179-20 Sec. 4.2 (Mod) / ASTM C149 | Shall not crack or break after tested per below<br>- prepare a cold-water bath at $21 \pm 1.1^{\circ}\text{C}$ ( $70 \pm 2^{\circ}\text{F}$ ).<br>- prepare a hot bath at $71 \pm 1.1^{\circ}\text{C}$ ( $160 \pm 2^{\circ}\text{F}$ )<br>- Immerse the sample completely in the hot water bath and allow to soak for $5 \text{ min} \pm 10 \text{ s}$ .<br>- transfer the sample to the cold bath, and immerse for at least 30 s.<br>- remove the sample from the cold bath and examine the sample for any cracking.<br>Note:<br>- the hot water that collects within the container during the first immersion shall be retained in the container through the second immersion<br>- the time of transfer from the hot bath to the cold bath shall be $15 \pm 1 \text{ s}$<br>Modification: sampling procedure not followed and expanded scope to all other glass products in addition to candle containers. | M PASS |

### REMARK:

1. No enclosed protocol for test results in this report.