















## 



# TEST REPORT

SHENZHEN JIERUIMA TRADING CO., LTD LAB LOCATION: NO.415 RUNLIAN BUILDING, SHENZHU ROAD, HENGGANG, 518115, SHENZHEN, CHINA LAB NUMBER:

SHENZHEN (8521)097-0435

ATTN: EMMA ZOU emma@cupwind.com

DATE IN: MOD. LOG IN: DATE OUT: REVISED DATE: WORKING DAYS: PAGE: APR 07, 2021 / APR 13, 2021 / 5 2 OF 4

	LL RATING
PASS	x
FAIL	
DATA	

# TESTING FOR CA 65 LEAD & CADMIUM ON NON-FOOD/ BEVERAGE GLASSWARE-EXTERIOR

Sample Description:	IRIDESC	ENT COATING CA	NDLE JAR			
Manufacturer:	CUPWIND COOPERATED FACILITY		P.O. No.:	/		
Buyer:	IPSY Style:		Louis			
Country of Origin:	CHINA Country of Destina		Country of Destination:	USA		
Color:	IRIDESCENT SKU N		SKU Number:	ITEM#: 9090		
Brand name:	CUPWINI	0.6		Commence of the commence of		
Re-test:	Yes:	No: X	Charge Vendor:	Yes: X No:		
Previous Report No.:	1					

### EXECUTIVE SUMMARY:

Test content CA 65 Lead & Cadmium on non-tood/beverage glassware-exterior			Result/Rating Meet/Pass		
Effectiveness of annealing	ASTM F2179-20 Sec. 4.2 (Mod)	With a tungsten carbide scribe, scratch once around the inside knucke of the article. Then scratch an "X" across the entire inside bottom surface of the article. All scratches are to be made using sufficient pressure to just penetrate the surface of the glass. Fill each article with water at the same room temperature as the glass. Walt if inhules, then empty the water and examine each piece for fractures. Shall show no fractures. Peport the number of fractures, if any, for each lest. Modification: expanded scope to all other glass products in addition to candle containers.		М	PASS
Thermal shock	ASTM F2179-20 Sec. 4.2 (Mod) / ASTM C149	products in addition to candle containers. Shall not crack or beak after lesish per below prepare a cold-water bath at 21±1.1°C (70±2°F), prepare a not bath at 71±1.1°C (160±2°F) - Immerse the sample completely in the hot water both and allow to soak for 5 min ±10 s transer the sample to the cold bath, and immerse for at each 30 s, - emrove the sample to make the cold bath, and immerse for at sea to 10 s, - emrove the sample for any cracking. Note: on the sample for any cracking. The container during the first immeration shall be retained in the container through the second immersion - the time of transer from the hot bath to the cold bath shall be 15±15. Modification: sampling procedure not followed and excended scope to all other class products.		М	PASS

#### REMARK:

1. No enclosed protocol for test results in this report.