

■

■

MOQ 500

■

■

■

■

1



Cupwind OEM / ODM



Wick Trimmer Cutter



Zinc Alloy Lid



Wooden Lid

MDF



TEST REPORT



8921087-0426 Page 3 of 4

TESTING FOR CA 85 LEAD & CADMIUM ON NON-FOOD BEVERAGE GLASSWARE-EXTERIOR

ATTN: EMMA ZOU
CUPWIND
DATE OUT: 2024-12-20
REVISED DATE: /
WORKING DAYS: 5
PAGE: 2 OF 4

OVERALL RATING
PASS
FAIL
DATA

TESTING FOR CA 85 LEAD & CADMIUM ON NON-FOOD BEVERAGE GLASSWARE-EXTERIOR

Sample Description:	IRIDESCENT COATING CANDELE JAR
Lot No:	10000
Country of Origin:	CHINA
Country of Destination:	USA
Color:	IRIDESCENT
SKU Number:	ITEM: 8090
Brand name:	CUPWIND®
Re-test:	Yes: <input type="checkbox"/> No: <input checked="" type="checkbox"/>
Change Vendor:	Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>
Previous Report No.:	7

Method	Reference	Result	Rating	Pass/Fail
Electrodes of arcing	ASTM F2179-20 Sec. 4.2 (M40)	Nil	M	PASS
Normal shock	ASTM F2179-20 Sec. 4.2 (M40) ASTM C149	Small not chips or break after tested per below - prepare a hot water bath at 211 ± 1 °C (410 ± 2 °F) - prepare a hot bath at 71 ± 1 °C (160 ± 2 °F) - immerse the sample completely in the hot water bath and allow to soak for 3 min ± 15 s. - transfer the sample to the cold bath and immerse for at least 30 s. - remove the sample from the cold bath and examine the sample for any cracking. Note: - The hot water that collects within the container during the first immersion shall be retained in the container through the second immersion. - The time of transfer from the hot bath to the cold bath shall be 15 ± 1 s. Modification: sampling procedure not followed and exceeded scope to all other glass products in addition to candle containers.	M	PASS

REMARK:
1. No enclosed protocol for test results in this report.

20

20

□□□□□□□□□□□□□□□□20□□□□□□□□□□□□□□

□□□□□□□□□□□□

