













ATTN:

TEST REPORT



(9521)097-0435 Page 3 of 4

SHENZHEN JIERUIMA TRADING CO., LTD NO.415 RUNLIAN BUILDING, SHENZHU ROAD, HENGGANG, 518115, SHENZHEN, CHINA

EMMA ZOU emma@cupwind.com

DATE IN: MOD. LOG IN: DATE OUT: REVISED DATE:

LAB LOCATION: LAB NUMBER:

APR 07, 2021 APR 13, 2021 5 2 OF 4

SHENZHEN (8521)097-0435

OVERALL RATING PASS FAIL DATA

TESTING FOR CA 65 LEAD & CADMIUM ON NON-FOOD/ BEVERAGE GLASSWARE EXTERIOR

Sample Description:	INIDESC	≘NTCOATING C	ANDLE JAH				
Manufacturer:	FACILITY	COOPERATED	P.O. No.:	/-			
Buyer:	IPSY		Style:	1			
Country of Origin:	CHINA		Country of Destination:	USA			
Color:	IRIDESCENT		SKU Number:	ITEM#: 9090			
Brand name:	CUPWINI	0.6					_
Re-test:	Yes:	No: X	Charge Vendor:	Yes:	X	No:	
Previous Report No.:	1						

EXECUTIVE SUMMARY:

Test content CA 65 Lead & C	Rating 388			
Effectiveness of annealing	ASTM F2179-20 Sec. 4.2 (Mod)	With a lungsten carbide scribe, scratch once around the inside knuckle of the article. Then scratch an "X" across the entire inside bottom surface of the article. All scratches are to be made using sufficient pressure to just penetrate the surface of the glass. Fill each article with water at the same room temperature as the glass. Wat 15 minutes, then empty the water and examine each piece for fractures. Shall show no fractures. Peport the number of fractures, if any, for each lest. Modification: expanded scope to all other glass products in addition to candle containers.		PASS
Thermal shock	ASTM F2179-20 Sec. 4.2 (Mod) / ASTM C149	Shall not crack or break after lessed per b- prepers a cod-water bath at 21±1.1°C (f 2°F). - prepers a hot bath at 71±1.1°C (f 0°F). - prepers a hot bath at 71±1.1°C (f 0°F). - minerse the sample completely in the h- water bath and slow to seak for 5 min±1 - transfer the sample for the cold bath, and timiserse for all tests 30 s, - emrove the sample for any cracking. Note: - the hot water that collects within the cond during the first immersion shall be retained the container through the second minersis - the time of transfer from the hot bath of to cold bath shall be 15±1 s Modification, sampling procedure not folio and expanded scope to all other glass pro in addition to candle containers.	2°F) xt 0 s. alher on he	PASS

1. No enclosed protocol for test results in this report.