

## 5oz Reed Diffuser Botol Kaca Borong



kekuatan kita

---

[China 5oz reed diffuser botol kaca borong](#)

10000 meter persegi pemilikan bengkel menghias.

20 jenis mesin menghias yang berbeza.

20 tahun pengalaman dalam bidang menghias.

20 kilang kaca bekerjasama stabil, kilang seramik, kilang kotak hadiah, kilang penutup logam, kilang penutup kayu menyokong.

Pembuatan jenama terkenal di seluruh dunia seperti Porsche, Armani, Zara dll.

ini [botol penyebar mewah](#) sesuai untuk promosi premium.

Tapak yang berat menjadikannya kelihatan mewah dan cantik.



## Ciri Produk

Terdapat kolar dan plag yang sepadan untuk botol peresap. Kami menawarkan warna kolar yang berbeza untuk pilihan. Garisan di bahagian bawah botol penyebar digunakan untuk memastikan botol kaca tidak pecah apabila disepuhlindap.



## Kesan proses



Cupwind menerima reka bentuk tersuai OEM/ODM. Kami boleh mencipta bentuk anda sendiri dengan/tanpa nama jenama. Hiasan yang tersedia untuk penyemburan, penyaduran elektrik, lukisan logam, pelekat, setem

panas, skrin sutera, sandblast, pemindahan air dll.



## TEST REPORT



(852)097-0435  
Page 3 of 4

SHENZHEN JIERUMA TRADING CO., LTD  
NO.415 RUILIAN BUILDING, SHENZHU ROAD,  
HENGGANG, 518115, SHENZHEN, CHINA

LAB LOCATION:

SHENZHEN  
(852)097-0435

LAB NUMBER:

ATTN: EMMA ZOU  
CUPWIND COOPERATED Co., Ltd.

PROD. NO.:  
DATE OUT:  
REVISED DATE:  
WORKING DAYS:

APR 13, 2021  
/ /  
200

### EXECUTIVE SUMMARY:

Test content: CA 65 Lead & Cadmium on non-food/beverage glassware-exterior Result/Rating: Meet/Pass

Semua pesanan kaca kami diuji oleh pihak ketiga.  
Biasanya kami menggunakan ujian Cat 65, ujian ASTM (Annealing and Thermal Shock), ujian Plumbeum dan Kadmium.

| OVERALL RATING |   |      |
|----------------|---|------|
| PASS           | X | FAIL |
| DATA           |   |      |

TESTING FOR  
CA 65 LEAD & CADMIUM ON NON-FOOD/  
BEVERAGE GLASSWARE-EXTERIOR

|                         |   |
|-------------------------|---|
| Sample Description:     | IRIDESCENT COATING CANDLE JAR   |
| Manufacturer:           | CUPWIND COOPERATED FACILITY   |
| Buyer:                  | IPSY  |
| Country of Origin:      | CHINA   |
| Color:                  | IRIDESCENT  |
| Brand name:             | CUPWIND ®   |
| Re-test:                | Yes: <input type="checkbox"/> No: <input checked="" type="checkbox"/> |
| Previous Report No.:    | /   |
| P.O. No.:               | /   |
| Style:                  | /   |
| Country of Destination: | USA   |
| SKU Number:             | ITEM# 8090  |

|                          |  |  |   |      |
|--------------------------|--|--|---|------|
| Effectiveness of coating | ASTM F2179-20<br>Sec. 4.2 (Mod)                | With a tungsten carbide sphere, scratch the surface of the article. Then apply an equal amount of pressure to the surface of the article. All scratches are to be made using sufficient pressure to just penetrate the surface of the test specimen's surface with a depth of 0.05 mm ± 0.01 mm. The time of application shall be 15 minutes on an empty tray with and examine each piece for fractures.   | M | PASS |
| Thermal shock            | ASTM F2179-20<br>Sec. 4.2 (Mod) /<br>ASTM C149 | Shall not crack or break after tested per below<br>- prepare a cold-water bath at 21±1.1°C (70±2°F)<br>- prepare a hot bath at 71±1.1°C (160±2°F)<br>- immerse the sample completely in the hot water and then break for 5 min ± 10 s.<br>- transfer the sample to the cold bath, and<br>immerse for at least 30 s.<br>- remove the sample from the cold bath and<br>examine the sample for any cracking.<br>Note:<br>The hot water that collects within the container during the first immersion shall be retained in the container through the second immersion<br>- the time of break from the hot bath to the cold bath shall be 15 ± 1 s.<br>Modification: sampling procedure not followed and expanded scope to all other glass products in addition to candle containers. | M | PASS |

### REMARK:

- No enclosed protocol for test results in this report.

## Proses pembungkusan dan palet



Kami membalut setiap satu kaca botol penyebar dengan beg opp untuk menjauhkan diri daripada habuk, kemudian karton beralun dengan pembahagi papan silang. Palet kayu sentiasa cekap untuk penghantaran LCL, dan kami akan menambah jaring kapas di tempat pintu untuk melindungi daripada jatuh apabila membuka pintu kontena.