

Square Reed Diffuser Glass Bottle Supplier



Our strength

[China Square Reed Diffuser Glass Bottle Supplier](#)

10000 square meters decorating workshop ownership.

20 kinds of different decorating machines.

20 years experience in the decorating area.

20+ stable cooperate glass factory, ceramic factory, gift box factory, metal lid factory, wooden lid factory supporting.

Worldwide famous brands making such as Porsche, Armani, Zara etc.

This [square diffuser bottle](#) holds 5.5oz fragrance, suitable for house, hotel, restaurant. The square shape makes the product classic and elegant.



Product Feature



Effect of process



Cupwind accepts OEM/ODM custom design. We can create your own shape with/without a brand name. The decoration available for spraying, electroplating, metallic painting, decal, hot stamping, silk screen, sandblast, water transfer etc.



TEST REPORT



(8521)097-0435
Page 3 of 4

SHENZHEN JIERUIMA TRADING CO., LTD
NO.415 RUNLIAN BUILDING, SHENZHU ROAD,
HENGGAANG, 518115, SHENZHEN, CHINA

LAB LOCATION: SHENZHEN
LAB NUMBER: (8521)097-0435

ATTN: EMMA ZOU
CC: emma@cupwind.com

DATE IN: APR 07, 2021
MOD. LOG IN: /
DATE OUT: APR 13, 2021
REVISED DATE: /
WORKING DAYS: 5
PAGE: 2 OF 4

EXECUTIVE SUMMARY:

Test content		Result Rating	
CA 65 Lead & Cadmium on non-food beverage glassware-exterior		Most/Pass	
Effectiveness of annealing	ASTM F2179-20 Sec. 4.2 (Mod)	M	PASS
With a tungsten carbide scribe, scratch once around the inside knuckle of the article. Then scratch an "X" across the entire inside bottom surface of the article. All scratches are to be made using sufficient pressure to just penetrate the surface of the glass. Fill each article with water at the same room temperature as the glass. Wait 15 minutes, then empty the water and examine each piece for fractures. Shall show no fractures. Report the number of fractures, if any, for each test.			
Thermal shock	ASTM F2179-20 Sec. 4.2.4 (Mod) ASTM C149	M	PASS
Shall not crack or break after tested per below procedure: - prepare a cold-water bath at $21 \pm 1^\circ\text{C}$ ($70 \pm 2^\circ\text{F}$) - immerse the sample completely in the hot water bath and allow to soak for $5 \text{ min} \pm 10 \text{ s}$. - transfer the sample to the cold bath, and immerse and hold for 10 seconds. - remove the sample from the cold bath and examine the sample for any cracking. Note: - the hot water that collects within the container during the first immersion shall be retained in the container through the second immersion - the time of transfer from the hot bath to the cold bath shall be $15 \pm 1 \text{ s}$ Modification: sampling procedure not followed and expanded scope to all other glass products in addition to candle containers.			

All of our glass orders are tested by a third party. Usually we go with Cali 65 Pro tests, ASTM (Annealing and Thermal Shock) tests, Lead and Cadmium tests.

OVERALL RATING	
PASS	
FAIL	
DATA	
TESTING FOR	
CA 65 LEAD & CADMIUM ON NON-FOOD / BEVERAGE GLASSWARE-EXTERIOR	
Sample Description: IRIDESCENT COATING SANDER JAR	P.O. No.: /
Manufacturer: CUPWIND COOPERATED FACILITY	Style: /
Buyer: IPSY	Country of Destination: USA
Country of Origin: CHINA	SKU Number: ITEM# 8090
Color: IRIDESCENT	
Brand name: CUPWIND®	
Re-test: Yes: <input type="checkbox"/> No: <input checked="" type="checkbox"/>	Charge Vendor: Yes: <input checked="" type="checkbox"/> No: <input type="checkbox"/>
Previous Report No.: /	

REMARK:

1. No enclosed protocol for test results in this report.

Packaging and pallet process



We wrap each [diffuser bottle glass](#) by an opp bag to keep away from dust, then corrugated cartons with cross board dividers. Wooden pallets are always efficient for LCL shipments, and we will add a cotton net in the door place to protect from falling when opening the container door.